Grout Re-Coloring Sealer

TECHNICAL DATA SHEET



PRODUCT BENEFITS:

- Highly Effective, Easy to Use, Innovative Water-Based Epoxy Sealer Formulation that Rejuvenates Old and Stained Grout.
- Provides Excellent Stain Protection with Beautiful Uniform Colored Grout.
- Keeps Grout Looking New and Makes On-going Maintenance Easier.
- Unique Low VOC formula (< 50 g/l).

USES:

- Sanded and Non-Sanded Cement, Epoxy and Urethane Grouts.
- Interior and Exterior applications.
- Floors, Walls and Countertops.

DIRECTIONS:

Read entire label before using. Use only as directed. **Always Test** in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for at least 28 days prior to application. Be sure surface is clean, thoroughly dry and free of sealers, coatings and contaminates before sealing.

SURFACE PREPARATION/REMOVAL:

- Existing Sealers – **OMNI Sealer Remover.**
- Existing Coatings/Waxes – **OMNI Heavy Duty Cleaner** or **OMNI Elite Cleaner.**
- Existing Contaminates – **OMNI Back-To-New Grout Cleaner, Buffer Acid Cleaner, Elite Cleaner, Deep Cleaner, Poultice Stain Remover** or **Sulfamic Acid Cleaner.**

APPLICATION STEPS:

Expert Tip: If more than 1 bottle of **Grout Re-Coloring Sealer** is to be used, mix multiple bottles together in a large container to ensure uniformity of color. Return product to original bottle for application.

1. **Shake well** before each use.
2. Unscrew Wheel-Applicator top and remove inner red seal from the neck of the bottle. Attach applicator top.
3. Hold bottle in a near vertical position, squeeze gently and continuously roll along the grout joint until the **Grout Re-Coloring Seale**r appears.
4. For hard to reach places such as around fixtures, corners or wide grout joints, use the Brush-Applicator (included).
5. Spread evenly using into joint using back-and-forth motion of Wheel-Applicator or Brush-Application. A soft bristle brush or a toothbrush can also be used.
6. Limit the amount of product that gets on the surface.
7. Before **Grout Re-Coloring Sealer** is completely dry (between 1 and 8 hours), lightly wet surface with water using a slightly dampened SpongaUSA™ sponge (included). A light spray mist of water can also be used.
8. Remove excess **Grout Re-Coloring Sealer** from surface using the yellow side of the scrubber sponge. Avoid scrubbing directly on the grout joint.
   Expert Tip: If **Grout Re-Coloring Sealer** is difficult to remove, use the yellow side of the scrubber sponge.
9. Some grout joints may require 2 or more coats, especially if changing from a dark to light grout color or when grout is badly discolored. Allow at least 4 hours between coats.
10. Surface is ready for traffic in 24 hours. Keep area dry for at least 72 hours. Avoid direct scrubbing on grout joints for 20 days.

SIZES:

8 oz. (other sizes available by special order).

COVERAGE:

Approx. 50 to 300 sq. ft. ($5m^2$ to $28m^2$) per 8 oz. depending on width and porosity of grout joint and size of surrounding tiles

TECHNICAL SUPPORT:

Call 949-709-5270, Monday thru Friday, 6:00am PT to 4:00pm PT or e-mail TechSupport@OMNI-Sealers.com.

EXPECTED WEAR:

Up to 15 years depending on type, density and texture of grout joint. Foot traffic, cleaning methods and weather can also affect wear.

MAINTENANCE:

- Routine Cleaning - **OMNI Concentrated Cleaner**.
- Periodic/Strong Cleaning – **OMNI Heavy Duty Cleaner or Deep Cleaner.**
- Problem Solving – **OMNI Back-T0-New-Grout Cleaner**, **Buffer Acid Cleaner, Efflorescence Remover, Elite Cleaner, Poultice Stain Remover or Sulfamic Acid Cleaner.**

COMPLIANCE AND HANDLING:

- Complies with all Federal, State and Local VOC regulatory requirements.
- Use and store between 40°F and 100°F (4°C and 38°C).
- Store in original container only and close after each use.
- Shelf life expected to be at least 1 year.

LIMITATIONS:

- Not recommended for use in pools, spas or areas subject to continuous underwater exposure.
- Harsh cleaners containing ammonia bleach, high-acid, high-alkaline or solvent can affect sealer's performance.
- Prevent sealer from contacting surrounding surfaces such as carpet, glass, landscaping, paint, metal and wood.

WARNINGS:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. If product gets in eyes, flush with water for at least 15 minutes. If product gets on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

KEEP OUT OF REACH OF CHILDREN

WARRANTY:

100% SATISFACTION GUARANTEED, when used as directed. Contact OMNI Sealers for exclusive remedy of either refund of purchase price or replacement of product. Proof of purchase within one year of purchase, required. Determining suitability of product for intended use shall be solely the responsibility of the user. There are no warranties, expressed or implied, including those of merchantability or fitness for a particular purpose, which is beyond the product description. In no case shall OMNI be liable for incidental or consequential damages.