

# Sealer Remover

## TECHNICAL DATA SHEET



### PRODUCT BENEFITS:

- Highly Effective, Multi-Purpose, Non-Flammable Stripper.
- Chemically Degrades Adhesion (breaks down) of Sealers and Contaminants.
- Long Dwell Time for Difficult Projects.
- Rinses Clean with Water.
- Easy to Use.

### USES:

- Tile, Stone, Concrete, Masonry & Grout Surfaces.
- Removes Adhesives, Coating Sealers, Deep-Set Stains, Epoxy Grout Haze & Residue, Grease, Lacquers, Paints, Penetrating Sealers, Sealer Residue, Urethane Grout Haze & Residue, Varnishes, Waxes & Floor Finishes and more.
- Interior and Exterior applications.

### DIRECTIONS:

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of application and desired results (see Limitations below).

### APPLICATION STEPS:

1. Apply **Sealer Remover** using a SpongaUSA™ sponge or a mop, paint-pad applicator, paint roller, or brush. Expert Tip: When using **Sealer Remover** on large projects, divide working area into manageable sections of approx. 25 sq. ft.
2. Allow **Sealer Remover** to dwell for up to 1 hour. Keep wet by adding additional **Sealer Remover**.
3. Agitate with a Primo Tools™ White Nylon Scrub Pad or other comparable non-marring scrubbing tool until achieve desired results.
4. Thoroughly rinse surface with water. A wet/dry vacuum may be used.
5. Some projects may require additional applications. Expert Tip: High-pressure (1000 – 3000psi) sprayers are highly effective at achieving desired results when used in conjunction with **Sealer Remover**.
6. Wipe surface completely dry using a clean, dry, white cotton towel or micro-fiber towel.
7. If surface is to be sealed, allow 24 hours drying time prior to applying a high quality OMNI sealer (see OMNI Product Recommendation Guide).

### SIZES:

Quarts, Gallons (other sizes available by special order).

### COVERAGE:

Approx. 75 to 200 sq. ft. (7.0m<sup>2</sup> to 18.62m<sup>2</sup>) per gallon depending on the type of surface, porosity, texture, temperature and method of application.

### TECHNICAL SUPPORT:

Call 949-709-5270, Monday thru Friday, 6:00am PT to 4:00pm PT or e-mail [TechSupport@OMNI-Sealers.com](mailto:TechSupport@OMNI-Sealers.com).

### COMPLIANCE AND HANDLING:

- Complies with all Federal, State and Local VOC regulatory requirements.
- Use and store between 40°F and 100°F (4°C and 38°C).
- Store in original container only and close after each use.
- Shelf life expected to be at least 1 year.

### LIMITATIONS:

- May damage synthetic agglomerate tiles or other solvent sensitive surfaces.
- Do not spray.
- Prevent product from contacting surrounding surfaces such as carpet, glass, landscaping, metal, paint and wood.

### WARNINGS:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. If product gets in eyes, flush with water for at least 15 minutes. If product gets on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

### KEEP OUT OF REACH OF CHILDREN

### WARRANTY:

100% SATISFACTION GUARANTEED, when used as directed. Contact OMNI Sealers for exclusive remedy of either refund of purchase price or replacement of product. Proof of purchase within one year of purchase, required. Determining suitability of product for intended use shall be solely the responsibility of the user. There are no warranties, expressed or implied, including those of merchantability or fitness for a particular purpose, which is beyond the product description. In no case shall OMNI be liable for incidental or consequential damages.