# SEALING GUIDE

## Basalt / Porphyry

**Classification:** Geological igneous formation, siliceous.
**Description:** A dark colored igneous rock with coarse and fine grained crystals.
**Density:** Hard.
**Porosity:** Slightly Porous (0.5% to 3.0%) to Moderately Porous (3.0% to 7.0%).
**Uses:** Interior walls and floors. Exterior walls and paving.
**Other:** Available in dark colors and multiple textures for high traffic applications.

OMNI™ SEALERS
Quality. Integrity. Support.

## SEALERS

| DESIRED RESULTS | OMNI OPTIONS | BENEFITS | EXP. WEAR | COATS | APPROX. COVERAGE | INT. | EXT. |
|---|---|---|---|---|---|---|---|
| Natural Appearance and Premium Stain Resistance | ELITE SEALER  | • Maximum Stain Protection, Especially in Food Prep and Service Areas.<br>• Preserves the Natural Appearance of the Surface.<br>• Makes On-Going Maintenance Easier. | 15 Yrs. | 2 | 800 – 1,100 sq. ft. per Coat per Gallon | Yes | Yes |
| Enhanced Appearance and Premium Stain Resistance | ENHANCING SEALER  | • Maximum Stain Protection, Especially in Food Prep and Service Areas.<br>• Darkens, Rejuvenates, Highlights and Enhances Unsealed Surfaces.<br>• Highly Fade-Resistant. | 15 Yrs. | 1 - 2 | 900 – 1,200 sq. ft. per Coat per Gallon | Yes | Yes |
| Low Gloss Appearance and Excellent Stain Resistance | LOW GLOSS SEALER  | • Excellent Stain Protection.<br>• Highly Durable Low Gloss Surface.<br>• Bonds to Itself for Touch-up and Reapplication. | 3 Yrs. | 2 | 800 – 1,100 sq. ft. per Coat per Gallon | Yes | Yes |
| High Gloss Appearance and Excellent Stain Resistance | HIGH GLOSS SEALER  | • Excellent Stain Protection.<br>• Highly Durable High Gloss Surface.<br>• Bonds to Itself for Touch-up and Reapplication. | 3 Yrs. | 2 | 800 – 1,100 sq. ft. per Coat per Gallon | Yes | No |
| Natural Appearance and Economical Stain Resistance | PENETRATING SEALER  | • Economical Stain Protection, Preserves Natural Appearance.<br>• Stain Resistance From Most Contaminates.<br>• Makes On-going Maintenance Easier. | 3 Yrs. | 2 | 800 – 1,100 sq. ft. per Coat per Gallon | Yes | Yes |

**EXPERT TIP:** At least 2 hours prior to grout installation, apply at least one coat of the "desired results" OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying "desired results" OMNI Sealer.

**Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail** TechSupport@OMNI-Sealers.com

**ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.**