SEALING GUIDE

Engineered Quartz

Classification: Manufactured - Factory.
Description: Blend of natural minerals w/made-made agents such as quartz and glass, mixed with polyester or epoxy resins.
Density: Hard (5 - 7 MOH).
Porosity: Slightly Porous (0.5% to 3.0%) to Moderately Porous (3.0% to 7.0%). Binder will affect porosity.
Uses: Interior walls, walls and countertops.
Other: Some colors and textures a susceptible to acid etching and may be susceptible to contaminants and staining.

OMNI™ SEALERS
Quality. Integrity. Support.

SEALERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
Natural Appearance and Premium Stain Resistance	ELITE SEALER 	• Maximum Stain Protection, Especially in Food Prep and Service Areas. • Preserves the Natural Appearance of the Surface. • Makes On-Going Maintenance Easier.	15 Yrs.	1 - 2	700 - 1,100 sq. ft. per Coat per Gallon	Yes	Yes
Enhanced Appearance and Premium Stain Resistance	ENHANCING SEALER 	• Maximum Stain Protection, Especially in Food Prep and Service Areas. • Darkens, Rejuvenates, Highlights and Enhances Unsealed Surfaces. • Highly Fade-Resistant.	15 Yrs.	1	800 - 1,200 sq. ft. per Coat per Gallon	Yes	Yes
Low Gloss Appearance and Excellent Stain Resistance	LOW GLOSS SEALER 	• Excellent Stain Protection. • Highly Durable Low Gloss Surface. • Bonds to Itself for Touch-up and Reapplication.	3 Yrs.	2	700 - 1,100 sq. ft. per Coat per Gallon	Yes	Yes
High Gloss Appearance and Excellent Stain Resistance	HIGH GLOSS SEALER 	• Excellent Stain Protection. • Highly Durable High Gloss Surface. • Bonds to Itself for Touch-up and Reapplication.	3 Yrs.	2	700 - 1,100 sq. ft. per Coat per Gallon	Yes	No
Natural Appearance and Economical Stain Resistance	PENETRATING SEALER 	• Economical Stain Protection, Preserves Natural Appearance. • Stain Resistance From Most Contaminates. • Makes On-going Maintenance Easier.	3 Yrs.	1 - 2	700 - 1,100 sq. ft. per Coat per Gallon	Yes	Yes

EXPERT TIP: At least 2 hours prior to grout installation, apply at least one coat of the "desired results" OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying "desired results" OMNI Sealer.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.