

SEALING GUIDE

Granite – Quartz Based (Exotics)

Classification: Geological. Metamorphic formation; siliceous.

Description: Crystalline quartz particles matrix with igneous characteristics and banding similar to veins.

Density: Hard (6 - 7 MOH).






Porosity: Slightly Porous (0.5% to 3.0%) to Moderately Porous (3.0% to 7.0%).

Uses: Interior walls, floors and countertops. Exterior veneer (cladding).

Other: Exotic granite can be brittle, limited tooling and edge detail option on countertops.



SEALERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE		<ul style="list-style-type: none"> • MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS. • PRESERVES THE NATURAL APPEARANCE OF THE SURFACE. • MAKES ON-GOING MAINTENANCE EASIER. 	15 YRS.	1 - 2	700 - 1,000 SQ. FT. PER COAT PER GALLON	YES	YES
ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE		<ul style="list-style-type: none"> • MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS. • DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES. • HIGHLY FADE-RESISTANT. 	15 YRS.	1	800 - 1,100 SQ. FT. PER COAT PER GALLON	YES	YES
LOW GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE		<ul style="list-style-type: none"> • EXCELLENT STAIN PROTECTION. • HIGHLY DURABLE LOW GLOSS SURFACE. • BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION. 	3 YRS.	2	700 - 1,000 SQ. FT. PER COAT PER GALLON	YES	YES
HIGH GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE		<ul style="list-style-type: none"> • EXCELLENT STAIN PROTECTION. • HIGHLY DURABLE HIGH GLOSS SURFACE. • BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION. 	3 YRS.	2	700 - 1,000 SQ. FT. PER COAT PER GALLON	YES	NO
NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE		<ul style="list-style-type: none"> • ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE. • STAIN RESISTANCE FROM MOST CONTAMINATES. • MAKES ON-GOING MAINTENANCE EASIER. 	3 YRS.	2	700 - 1,000 SQ. FT. PER COAT PER GALLON	YES	YES

EXPERT TIP: At least 2 hours prior to grout installation, apply at least one coat of the “desired results” OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying “desired results” OMNI Sealer.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.