

# SEALING GUIDE

## Limestone - Honed

**Classification:** Geological. Sedimentary formation; calcareous.

**Description:** Typical varieties exhibit minimal graining or directional movement.

**Density:** Medium to Hard (3 - 5 MOH.)











**Porosity:** Slightly Porous (0.5% to 3.0%) to Highly Porous (>7.0%).

**Uses:** Interior walls, floors and countertops. Exterior limited to mild climate.

**Other:** Matte finish (little or no gloss) achieve through chemicals, abrasives and machinery. May etch or lighten, if exposed to acid.



## SEALERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE	 	<ul style="list-style-type: none"> <li>• MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>• PRESERVES THE NATURAL APPEARANCE OF THE SURFACE.</li> <li>• MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	15 YRS.	2	500 - 1,000 SQ. FT. PER COAT PER GALLON	YES	YES
ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE	 	<ul style="list-style-type: none"> <li>• MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>• DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES.</li> <li>• HIGHLY FADE-RESISTANT.</li> </ul>	15 YRS.	1 - 2	600 - 1,100 SQ. FT. PER COAT PER GALLON	YES	YES
LOW GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE	 	<ul style="list-style-type: none"> <li>• EXCELLENT STAIN PROTECTION.</li> <li>• HIGHLY DURABLE LOW GLOSS SURFACE.</li> <li>• BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION.</li> </ul>	3 YRS.	2	500 - 1,000 SQ. FT. PER COAT PER GALLON	YES	YES
HIGH GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE	 	<ul style="list-style-type: none"> <li>• EXCELLENT STAIN PROTECTION.</li> <li>• HIGHLY DURABLE HIGH GLOSS SURFACE.</li> <li>• BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION.</li> </ul>	3 YRS.	2	500 - 1,000 SQ. FT. PER COAT PER GALLON	YES	NO
NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE	 	<ul style="list-style-type: none"> <li>• ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE.</li> <li>• STAIN RESISTANCE FROM MOST CONTAMINATES.</li> <li>• MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	3 YRS.	2	500 - 1,000 SQ. FT. PER COAT PER GALLON	YES	YES

**EXPERT TIP:** At least 2 hours prior to grout installation, apply at least one coat of the “desired results” OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying “desired results” OMNI Sealer.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail [TechSupport@OMNI-Sealers.com](mailto:TechSupport@OMNI-Sealers.com)

**ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.**