SEALING GUIDE

Marble - Tumbled

Classification: Geological. Metamorphic formation; calcareous.
Description: Composed predominantly of crystalline grains of calcite.
Density: Medium to Hard (4 - 5 MOH).
Porosity: Moderately Porous (3.0% to 7.0%) to Highly Porous (>7.0%).
Uses: Interior walls, countertops, and floors. Exterior limited to mild climate.
Other: Weathered finish achieved through tumbling stone w/sand, pebbles or steel bearings. May etch or lighten, if exposed to acid.

OMNI™ SEALERS
Quality. Integrity. Support.

SEALERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
Natural Appearance and Premium Stain Resistance	ELITE SEALER 	• Maximum Stain Protection, Especially in Food Prep and Service Areas. • Preserves the Natural Appearance of the Surface. • Makes On-Going Maintenance Easier.	15 Yrs.	2	700 - 1,000 Sq. Ft. per Coat per Gallon	Yes	Yes
Enhanced Appearance and Premium Stain Resistance	ENHANCING SEALER 	• Maximum Stain Protection, Especially in Food Prep and Service Areas. • Darkens, Rejuvenates, Highlights and Enhances Unsealed Surfaces. • Highly Fade-Resistant.	15 Yrs.	1 - 2	800 – 1,100 Sq. Ft. per Coat per Gallon	Yes	Yes
Low Gloss Appearance and Excellent Stain Resistance	LOW GLOSS SEALER 	• Excellent Stain Protection. • Highly Durable Low Gloss Surface. • Bonds to Itself for Touch-up and Reapplication.	3 Yrs.	2	700 - 1,000 Sq. Ft. per Coat per Gallon	Yes	Yes
High Gloss Appearance and Excellent Stain Resistance	HIGH GLOSS SEALER 	• Excellent Stain Protection. • Highly Durable High Gloss Surface. • Bonds to Itself for Touch-up and Reapplication.	3 Yrs.	2	700 - 1,000 Sq. Ft. per Coat per Gallon	Yes	No
Natural Appearance and Economical Stain Resistance	PENETRATING SEALER 	• Economical Stain Protection, Preserves Natural Appearance. • Stain Resistance From Most Contaminates. • Makes On-going Maintenance Easier.	3 Yrs.	2	700 - 1,000 Sq. Ft. per Coat per Gallon	Yes	Yes

EXPERT TIP: At least 2 hours prior to grout installation, apply at least one coat of the "desired results" OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying "desired results" OMNI Sealer.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.