

SEALING GUIDE

Salttilo

Classification: Manufactured - Factory.

Description: Rustic appearance made w/natural clay (terra cotta) and fired at low temps. Typically from Saltillo, Mexico.

Density: Soft to Medium.











Porosity: Highly Porous (>7.0%).

Uses: Interior walls and floors. Exterior paving in mild climate. Not recommended for wet areas.

Other: Highly susceptible to contaminants and stains.



SEALERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE	 	<ul style="list-style-type: none"> • MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS. • PRESERVES THE NATURAL APPEARANCE OF THE SURFACE. • MAKES ON-GOING MAINTENANCE EASIER. 	15 YRS.	2 - 3	400 - 600 SQ. FT. PER COAT PER GALLON	YES	YES
ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE	 	<ul style="list-style-type: none"> • MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS. • DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES. • HIGHLY FADE-RESISTANT. 	15 YRS.	2 - 3	500 - 700 SQ. FT. PER COAT PER GALLON	YES	YES
LOW GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE	 	<ul style="list-style-type: none"> • EXCELLENT STAIN PROTECTION. • HIGHLY DURABLE LOW GLOSS SURFACE. • BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION. 	3 YRS.	3 - 4	400 - 600 SQ. FT. PER COAT PER GALLON	YES	YES
HIGH GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE	 	<ul style="list-style-type: none"> • EXCELLENT STAIN PROTECTION. • HIGHLY DURABLE HIGH GLOSS SURFACE. • BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION. 	3 YRS.	3 - 4	400 - 600 SQ. FT. PER COAT PER GALLON	YES	NO
NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE	 	<ul style="list-style-type: none"> • ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE. • STAIN RESISTANCE FROM MOST CONTAMINATES. • MAKES ON-GOING MAINTENANCE EASIER. 	3 YRS.	2 - 3	400 - 600 SQ. FT. PER COAT PER GALLON	YES	YES

EXPERT TIP: At least 2 hours prior to grout installation, apply at least one coat of the “desired results” OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying “desired results” OMNI Sealer.

Technical Support: 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail TechSupport@OMNI-Sealers.com

ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.