

# SEALING GUIDE

## Terra Cotta

**Description:** Rustic appearance made with natural clay fired at low temperatures. Can be glazed or unglazed.

**Density:** Medium.

**Porosity:** Moderately Porous (3.0% to 7.0%) to Highly Porous (>7.0%). Glaze results in significantly lower porosity.

**Uses:** Interior walls and floors. Exterior paving and veneer (cladding) in mild climate.

**Other:** Unglazed highly susceptible to contaminates and stains. Glazed may be susceptible to contaminates and stains.



## SEALERS

DESIRED RESULTS	OMNI OPTIONS	BENEFITS	EXP. WEAR	COATS	APPROX. COVERAGE	INT.	EXT.
NATURAL APPEARANCE AND PREMIUM STAIN RESISTANCE		<ul style="list-style-type: none"> <li>• MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>• PRESERVES THE NATURAL APPEARANCE OF THE SURFACE.</li> <li>• MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	15 YRS.	2 - 3	600 - 800 SQ. FT. PER COAT PER GALLON	YES	YES
ENHANCED APPEARANCE AND PREMIUM STAIN RESISTANCE		<ul style="list-style-type: none"> <li>• MAXIMUM STAIN PROTECTION, ESPECIALLY IN FOOD PREP AND SERVICE AREAS.</li> <li>• DARKENS, REJUVENATES, HIGHLIGHTS AND ENHANCES UNSEALED SURFACES.</li> <li>• HIGHLY FADE-RESISTANT.</li> </ul>	15 YRS.	2 - 3	700 - 900 SQ. FT. PER COAT PER GALLON	YES	YES
LOW GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE		<ul style="list-style-type: none"> <li>• EXCELLENT STAIN PROTECTION.</li> <li>• HIGHLY DURABLE LOW GLOSS SURFACE.</li> <li>• BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION.</li> </ul>	3 YRS.	3 - 4	600 - 800 SQ. FT. PER COAT PER GALLON	YES	YES
HIGH GLOSS APPEARANCE AND EXCELLENT STAIN RESISTANCE		<ul style="list-style-type: none"> <li>• EXCELLENT STAIN PROTECTION.</li> <li>• HIGHLY DURABLE HIGH GLOSS SURFACE.</li> <li>• BONDS TO ITSELF FOR TOUCH-UP AND REAPPLICATION.</li> </ul>	3 YRS.	3 - 4	600 - 800 SQ. FT. PER COAT PER GALLON	YES	NO
NATURAL APPEARANCE AND ECONOMICAL STAIN RESISTANCE		<ul style="list-style-type: none"> <li>• ECONOMICAL STAIN PROTECTION, PRESERVES NATURAL APPEARANCE.</li> <li>• STAIN RESISTANCE FROM MOST CONTAMINATES.</li> <li>• MAKES ON-GOING MAINTENANCE EASIER.</li> </ul>	3 YRS.	2 - 3	600 - 800 SQ. FT. PER COAT PER GALLON	YES	YES

**EXPERT TIP:** At least 2 hours prior to grout installation, apply at least one coat of the “desired results” OMNI Sealer to surface as a **Pre-Grout Sealer**. Makes grout installation and clean-up easier and faster, while protecting surface from grout stains. Allow new grout to cure at least 48 hours prior applying “desired results” OMNI Sealer.

**Technical Support:** 949-709-5270 Mon thru Fri 6:00am PT to 4:00pm PT and/or E-mail [TechSupport@OMNI-Sealers.com](mailto:TechSupport@OMNI-Sealers.com)

**ALWAYS TEST IN A SMALL INCONSPICUOUS AREA.**